


**hydraut**

hydraut.com

## HYDRAULIC PISTON PUMPS PQ SERIES



Working pressure: up to 250 bar  
Peak pressure: up to 280 bar  
Displacements: from 8cc to 70cc

**AXIAL PISTON PUMP****PQ SERIES**

nominal pressure: 250bar  
max. pressure: 280 bar

1. PQ Series pump, new design for changeable angle of swash plate, wide applications.
2. Special design, low noise level during full pressure time.
3. Modular control, easy to design system, advantages are: power saving, small size, low cost.
4. Low power consuming, low oil temperature rising, suitable application for assembling small power units.

**Specifications**

Size	Model	Displacement at ( 7 bar ) 100 PSI					Pressure Adj.			Speed		Weight
		cm <sup>3</sup> /rev	In <sup>3</sup> /rev	1500 RPM LPM	U.S. GPM	1800 RPM LPM	U.S. GPM	kgf/cm <sup>2</sup>	Max. RPM	Min. RPM		
1	PQ 8	8.0	0.48	12.0	3.17	14.4	3.8	1: 8~70 2: 15~140 3: 20~210 4: 20~250	1800	500	13 (28.6)	13 (28.6)
	PQ 10	10.0	0.61	15.0	3.90	18.0	4.76				13 (28.6)	
	PQ 15	15.0	0.90	22.5	5.78	27.0	7.05				13 (28.6)	
	PQ 18	17.8	1.09	26.7	7.05	32.0	8.45				13 (28.6)	
2	PQ 23	23.0	1.40	35.4	9.11	41.4	10.94	1: 8~70 2: 15~140 3: 20~210 4: 20~250	1800	500	22 (48.4)	22 (48.4)
	PQ 25	25.0	1.52	37.5	9.66	45.0	11.60				22 (48.4)	
3	PQ 38	37.8	2.31	56.7	14.98	68.0	17.96				26 (57.2)	26 (57.2)
	PQ 42	42.0	2.56	63.0	16.23	76.0	19.58				26 (57.2)	
4	PQ 50	51.5	3.14	77.2	20.37	92.7	24.48	1: 8~70 2: 15~140 3: 20~210	1800	500	56 (123.2)	56 (123.2)
	PQ 70	69.7	4.25	104.5	27.6	125.4	33.10				56 (123.2)	

1. Install outlet on top, the pipe pressure needs less than 2bar.
2. Using at max. pressure, please undre 6 sec for per-cycle time.
3. Hydraulic oil clean, please following instruction manual.
4. HYDRAUT supply combinable pumps with different series, standard with Metric / SAE size.

# AXIAL PISTON PUMP

## PQ SERIES

### TYPE CODE FOR STANDARD PROGRAM

<b>PQ</b>	15	A	3	R	6	7	-	8	9	10	11	12	13	14
Series	Size and displacement	Control device	Pressure adjusting	Rotation	Direction of pipe connections	Shaft type	Voltage	Threads type	Thru drive & 2nd pump	Special spec.	Mounting	Seals	Design No.	

#### Series

1	Axial piston pump variable displacement high pressure version	nominal pressure: 250 bar max. pressure: 280 bar version rear threaded port	PQ
			PQR

2	Code	8	10	15	18	23	25	38	42	50	70
	Size						2		3		4
	Displacement cm³ / rev	8	10	15	18	23.0	25.0	37.8	42.0	51.5	69.7
	In³ / rev	0.48	0.61	0.90	1.1	1.40	1.52	2.31	2.56	3.14	4.25

#### Control device

3	Standard pressure control	A
	Remote pressure control	G
	Pressure	
	A Low : 7 bar	
	B Mid : 14 bar	
	C High : 21 bar	
	Load-sensing control	HL
	Muti-stage flow & Singe-stage pressure control (with cylinder)	B
	2-stage pressure & Flow control	C
	2-stage pressure & Flow control + Remote	CG
	2-stage pressure & Flow control + Low tension unloading	CR
	Low tension unloading + Pressure control	D
	Low tension unloading + Pressure control + Remote	DG
	Electric 2-stage pressure control	E
	Electric 2-stage pressure control + Remote	EG
	Electric 2-stage pressure control & Flow control	F
	Electric 2-stage pressure control & Flow control + Remote	FG
	Remote pressure compensator with NG6 interface	GM
	Remote pressure compensator + Proportional pressure valve	GJ
	Remote pressure compensator + Electrical unloading	GR
	Remote pressure compensator + 2-stage pressure control	GB
	Remote pressure compensator + Electrical unloading + 2-stage pressure control	GC
	Pressure	
	A Low : 7 bar	HQ
	B Mid : 14 bar	
	C High : 21 bar	
	Load-sensing compensator + Proportional flow valve + Relief valve	
	Pressure	
	A Low : 7 bar	HK
	B Mid : 14 bar	
	C High : 21 bar	
	Load-sensing compensator + Proportional pressure valve + Proportional flow valve	

# AXIAL PISTON PUMP

## PQ SERIES

### TYPE CODE FOR STANDARD PROGRAM

1	15	A	3	R	6	7	-	8	9	10	11	12	13	14
Series	Size and displacement	Control device	Pressure adjusting	Rotation	Direction of pipe connections	Shaft type	Voltage	Threads type	Thru drive & 2nd pump	Special spec.	Mounting	Seals	Design No.	

### Pressure adjusting

4	8~70 bar (0.8~6.9 Mpa)	1
	15~140 bar (1.5~13.7 Mpa)	2
	20~210 bar (2.0~20.6 Mpa)	3
	20~250 bar (2.0~24.5 Mpa )	4

### Rotation

5	Clockwise	R
	Counter clockwise	L

### Direction of pipe connections

6	None: Side port (Flange)	8	10	15	18	23	25	38	42	50	70		*
	Rear port (Flange)	■	■	■	■	■	■	■	■	■	■	B	
	Side port + Rear port (Flange)	■	■	■	■	■	■	■	■	■	■	B2	

B2 valid only for pumps from 23 to 70 cc/rev

### Shaft type

7	Displacement	Code											
	None	Key:											
	PQ15, PQ18	Splind shaft:	S	13T 16/32 DP	S1	9T 16/32 DP	S2	11T 16/32 DP					
	PQ23, PQ25 PQ38, PQ42	Splind shaft:	S	13T 16/32 DP	S1	15T 16/32 DP							
	PQ50, PQ70	Splind shaft:	S	14T 12/24 DP									

### Voltage

8	None												
	AC100V (50/60HZ)											A	
	AC110V (60HZ)											B	
	AC220V (50/60HZ)											C	
	AC220V (60HZ)											D	
	DC 12V											E	
	DC 24V											F	*

■ = available - = on request \* = standard type △ = custom made

# AXIAL PISTON PUMP

## PQ SERIES

### TYPE CODE FOR STANDARD PROGRAM

<b>PQ</b>	15	A	3	R	6	7	-	8	9	10	11	12	13	14
1	2	3	4	5	6	7		Voltage	Threads type	Thru drive & 2nd pump	Special spec.	Mounting	Seals	Design No.

Series      Size and displacement      Control device      Pressure adjusting      Rotation      Direction of pipe connections      Shaft type

### Threads

9	PT (RC)	■	■	■	■	■	■	■	■	■	■	■	■	■	■	10	※
	BSPP (G)	■	■	■	■	■	■	■	■	■	■	■	■	■	■	40	※
	NPT	△	△	△	△	△	△	△	△	△	△	△	△	△	△	50	※
	UNF (SAE o-ring)	■	■	■	■	■	■	■	■	■	■	■	■	■	■	60	※
	Metric	△	△	△	△	△	△	△	△	△	△	△	△	△	△	70	※

### Thru drive & 2nd pump

10	without Thru drive																※
	Ø 50.8 mm SAE AA	■	■	■	■	■	■	■	■	■	■	■	■	■	■	C	
	Ø 82.55 mm SAE A	■	■	■	■	■	■	■	■	■	■	■	■	■	■	D	
	Ø 101.6 mm SAE B	△	△	△	△	△	△	△	△	△	△	△	△	△	△	E	
	Ø 127 mm	■	■	■	■	■	■	■	■	■	■	■	■	■	■	F	
	Ø 63 mm	■	■	■	■	■	■	■	■	■	■	■	■	■	■	I	
	Ø 80 mm	■	■	■	■	■	■	■	■	■	■	■	■	■	■	J	
	Ø 100 mm	■	■	■	■	■	■	■	■	■	■	■	■	■	■	K	
	Ø 125 mm	■	■	■	■	■	■	■	■	■	■	■	■	■	■	L	

(Please contact HYDRAUT, if other size required.)

### Special specification

11	Standard type														X	※
	Low Pressure type														X1	
	Deahead pressure relief type														Z	

### Mounting

12	Only for PQ15, PQ18 can select "A", other displacement only select "None: Standard"	None : Standard														※
		SAE A 2 bolt													A	

### Seals

13	NBR															※
		VITON													A	

■ = available   - = on request   ✽ = standard type   △ = custom made

# AXIAL PISTON PUMP

## PQ SERIES

### CONTROL TYPE

Controls	Symbol	Characteristic	Specifications
A type: Standard pressure control			<p>1. When system pressure increase and reach present pressure the flow decrease automatically and pressure to be constant.      2. Pressure and flow can be adjusted manually.</p>
G type: Remote pressure control			<p>1. The same function of "A" control type.      2. Pressure can be adjusted remotely by the remote control valve.</p>
HL type: Load-sensing control			<p>1. HL valve with 2 different pressure, control displacement.      2. The flow can be changed by HL valve, the sensing feedback can reach low oil temperature and energy saving.</p>
B type: Multi-stage flow & Single-stage pressure control (with cylinder)			<p>1. Flow can be adjusted from 0 to maximum and pressure can be maintaining at preset pressure.      2. Absorbing impact and vibration which are produced by up down motions.      It is suitable for lifting equipment etc.</p>
C type: 2-stage pressure & Flow control			<p>1. 2-stage pressure to adjust PL to QH and : PH to QL.      2. When pressure increase and reach preset pressure "PH", flow is reduced to "QL".      3. Adapt for long dead head and short pressurizing machines, speedy and energy saving.      4. Pressure "PH""PL", and flow "QH""QL"can be adjusted optionally.</p>
CG type: 2-stage pressure & Flow control + Remote			<p>1. The same function of "C" control type.      2. The pressure and the range can be adjusted by remote control valve.      3. Install HYDRAUT solenoid control valve to reach good performance.</p>

# AXIAL PISTON PUMP

## PQ SERIES

### CONTROL TYPE

Controls	Symbol	Characteristic	Specifications
CR type: 2-stage pressure & Flow control + Low tension unloading		 SOL OFF: Low tension unloading SOL ON: 2-stage pressure&flow	1. Install HYDRAUT solenoid valve, control 2-stage pressure. 2. It is suitable for constant speed lifting equipments, and setting 2-stage working pressure. 3. PL and PH, two options can be PH.
D type: Low tension unloading + Pressure control		 P →	1. Same as type A and with low tension unloading. 2. It is adapt for long unloading operation. 3. When the system stops, oil temperature and noise maintain low level while being through the unloading.
DG type: Low tension unloading + Pressure control + Remote		 P → PH	1. The same function of "D" control type. 2. The pressure and the range can be adjusted by remote control valve. 3. Install HYDRAUT solenoid control valve to reach good performance.
E type: Electric 2-stage pressure control		 PL P →	1. 2-stage pressure is controlled by solenoid control valve. 2. Adapt for constant speed lifting equipments, and setting 2-stage working pressure. 3. PL and PH, two options can be PH.
EG type: Electric 2-stage pressure control + Remote		 PL P →	1. The same function of "E" control type. 2. The pressure and the range can be adjusted by remote control valve. 3. Install HYDRAUT solenoid control valve to reach good performance.
F type: Electric 2-stage pressure control & Flow control		 QH QL PL P → PH	1. Electric 2-stage pressure & flow control to adjust PL to QH, PH to QL. 2. Pressure "PL", "PH" and flow "QH" can be adjusted optionally.

# AXIAL PISTON PUMP

## PQ SERIES







### CONTROL TYPE

Controls	Symbol	Characteristic	Specifications
FG type: Electric 2-stage pressure control & Flow control + Remote		 PL → PH QL → QH SOL OFF → SOL ON	1. Electric 2-stage pressure & flow control to adjust PL to QH, PH to QL. 2. Pressure can be adjusted by remote control valve. 3. Pressure "PL", "PH" and flow "QH" can be adjusted optionally.
GM type: Remote pressure compensator with NG6 interface		 P → Q	1. GM Remote pressure compensator with NG6 interface. 2. Speedy reactions, stable pressure supply. 3. Adapt for manual or electric control.
GJ type: Remote pressure compensator + Proportional pressure valve		 P → Q	1. Same as type "GM" and with proportional pressure valve. 2. The proportional valve is installed on the NG6 interface to reach proportional electric control to save energy.
GR type: Remote pressure compensator + Electrical unloading		 P → Q SOL "OFF" → SOL "ON"/>	1. By adding a relief valve and solenoid control valve on the compensator makes pump have both function. 2. GR control is for long unloading situations. When the system stops, oil temperature and noise maintain low level while being through the unloading.
GB type: Remote pressure compensator + 2-stage pressure control		 P → Q SOL "OFF" → SOL "ON"/> Select PL or PH to be high pressure	1. By adding a relief valve and solenoid control valve on the compensator makes pump have both function. 2. GB control is for Z-stage working pressure under the constant cylinder speed.

# AXIAL PISTON PUMP

## PQ SERIES

### CONTROL TYPE


Controls	Symbol	Characteristic	Specifications
GC type: Remote pressure compensator + Electrical unloading + 2-stage pressure control		 <p>Select PL or PH to be high pressure</p>	<p>1. Control two different-stage limited pressure by adding solenoid valve and unloading function.      2. When the system stops, oil temperature and noise maintain low level by unloading function.      3. Adapt for stable cylinder speed, 2-stage pressure, and long unloading situation.</p>
HQ type: Load-sensing compensator + Proportional flow valve + Relief valve			<p>1. HQ control with load-sensing and proportional flow control.      2. By electric input signal to adjust pump displacement, and the flow is controlled by electric modular control.</p>
HK type: Load-sensing compensator + Proportional pressure valve + Proportional flow valve			<p>1. HK offers the smallest pressure and flow according to different requirement.      2. The displacement is nearly zero when the system stands by, and the motor output is also nearly zero to saving energy.      3. When the system reaches setting pressure, the pump displacement will reduce by itself.      It only needs to add the system required flow, and the pressure remains the same which control the oil temperature.      4. Compared with vane pump, gear pump + PQ valve can save 30-50% energy.</p>

## AXIAL PISTON PUMP


### PQ SERIES

#### DIMENSION

**PQ15A, PQ18A** - Standard pressure control



**PQ15G, PQ18G** - Remote pressure control




## AXIAL PISTON PUMP

### PQ SERIES


#### DIMENSION

**PQ15HL, PQ18HL** - Load-sensing control




**PQ15B, PQ18B** - Multi-stage flow & Single-stage pressure control (with cylinder)

(Remark : Install with A type control)



**PQ15C, PQ18C** - 2-stage pressure & Flow control




## AXIAL PISTON PUMP


### PQ SERIES

#### DIMENSION


**PQ15CG, PQ18CG** - 2 - stage pressure & Flow control + Remote



**PQ15CR, PQ18CR** - 2 - stage pressure & Flow control + Low tension unloading



**PQ15D, PQ18D** - Low tension unloading + Pressure control




## AXIAL PISTON PUMP


## PQ SERIES

### DIMENSION


**PQ15DG, PQ18DG** - Low tension unloading + Pressure control + Remote



**PQ15E, PQ18E** - Electric 2 - stage pressure control



**PQ15EG, PQ18EG** - Electric 2 - stage pressure control + Remote




## AXIAL PISTON PUMP


## PQ SERIES

### DIMENSION


**PQ15F, PQ18F** - Electric 2 - stage pressure control & Flow control



**PQ15FG, PQ18FG** - Electric 2 - stage pressure control & Flow control + Remote



**PQ15GM, PQ18GM** - Remote pressure compensator with NG6 interface




## AXIAL PISTON PUMP


## PQ SERIES

### DIMENSION


**PQ15GJ, PQ18GJ** - Remote pressure compensator + Proportional pressure valve



**PQ15GR, PQ18GR** - Remote pressure compensator + Electrical unloading



**PQ15GB, PQ18GB** - Remote pressure compensator + 2-stage pressure control




## AXIAL PISTON PUMP


## PQ SERIES

### DIMENSION


**PQ15GC, PQ18GC** - Remote pressure compensator + Electrical unloading + 2-stage pressure control



**PQ15HQ, PQ18HQ** - Load-sensing compensator + Proportional flow valve + Relief valve



**PQ15HK, PQ18HK** - Load-sensing compensator + Proportional pressure valve + Proportional flow valve




## AXIAL PISTON PUMP

### PQ SERIES

#### DIMENSION

**PQ15, PQ18** - Thru drive (SAE AA  $\varnothing 50.8$ , code C)  
 Thru drive (SAE A  $\varnothing 82.55$ , code D)


PQ	15	□	□	□	□	—	□	□	C	□	□
PQ	15	□	□	□	□	—	□	□	D	□	□



Type	A	B	C	CG	CR	D	DG	E	EG	F	FG	G	GJ	GM	HL	HK	HQ
○ Thru drive option	○					○	○	○	○			○	○	○	○	○	○

#### PQ15, PQ18 - Splined shaft type

#### PQ15, PQ18 - Inlet / Outlet



S: 11T DP16/32

S1: 9T DP16/32


S2: 13T DP16/32

## AXIAL PISTON PUMP


## PQ SERIES

### DIMENSION


**PQ23A, PQ25A** - Standard pressure control



**PQ23G, PQ25G** - Remote pressure control



**PQ23HL, PQ25HL** - Load-sensing control




# AXIAL PISTON PUMP


## PQ SERIES

### DIMENSION


**PQ23B, PQ25B** - Multi-stage flow & Single-stage pressure control (with cylinder)



**PQ23C, PQ25C** - 2-stage pressure & Flow control




**PQ23CG, PQ25CG** - 2-stage pressure & Flow control + Remote




**AXIAL PISTON PUMP****PQ SERIES****DIMENSION**


**PQ23CR, PQ25CR** - 2-stage pressure & Flow control + Low tension unloading



**PQ23D, PQ25D** - Low tension unloading + Pressure control



**PQ23DG, PQ25DG** - Low tension unloading + Pressure control + Remote




## AXIAL PISTON PUMP


## PQ SERIES

### DIMENSION


**PQ23E, PQ25E** - Electric 2-stage pressure control



**PQ23EG, PQ25EG** - Electric 2-stage pressure control + Remote



**PQ23F, PQ25F** - Electric 2-stage pressure control & Flow control




## AXIAL PISTON PUMP


## PQ SERIES

### DIMENSION


**PQ23FG, PQ25FG** - Electric 2-stage pressure control & Flow control + Remote



**PQ23GM, PQ25GM** - Remote pressure compensator with NG6 interface



**PQ23GJ, PQ25GJ** - Remote pressure compensator + Proportional pressure valve




## AXIAL PISTON PUMP


## PQ SERIES

### DIMENSION


**PQ23GR, PQ25GR** - Remote pressure compensator + Electrical unloading



**PQ23GB, PQ25GB** - Remote pressure compensator + 2-stage pressure control



**PQ23GC, PQ25GC** - Remote pressure compensator + Electrical unloading + 2-stage pressure control




## AXIAL PISTON PUMP


## PQ SERIES

### DIMENSION

**PQ23HQ, PQ25HQ** - Load-sensing compensator + Proportional flow valve + Relief valve




**PQ23HK, PQ25HK** - Load-sensing compensator + Proportional pressure valve + Proportional flow valve



**PQ23, PQ25** - Thru drive(SAE A Ø82.55, code D)  
Thru drive(SAE B Ø101.6, code E)

Type	A	B	C	CG	CR	D	DG	E	EG	F	FG	G	GJ	GM	HL	HK	HQ
<input type="radio"/> Thru drive option	<input type="radio"/>																
<input checked="" type="radio"/> Thru drive	<input type="radio"/>																




## AXIAL PISTON PUMP


## PQ SERIES

### DIMENSION

**PQ23, PQ25 - Rear port** (Please flowing order code no.6, add "B")




**PQ23, PQ25 - 4 Connections for rear port** (Please flowing order code no.6, add "B2")




Type	A	B	C	CG	D	DG	E	EG	F	FG	G	GJ	GM	HL	HK	HQ
○ Axial port option	○	○									○	○	○	○		

**PQ23, PQ25 - Splined shaft type**



**PQ23, PQ25 - Inlet / Outlet**




## AXIAL PISTON PUMP


**PQ SERIES**

### DIMENSION


**PQ38A, PQ42A** - Standard pressure control



**PQ38G, PQ42G** - Remote pressure control



**PQ38HL, PQ42HL** - Load-sensing control




# AXIAL PISTON PUMP


## PQ SERIES

### DIMENSION


**PQ38B, PQ42B** - Multi-stage flow & Single-stage pressure control (with cylinder)






**PQ38C, PQ42C** - 2-stage pressure & Flow control



**PQ38CG, PQ42CG** - 2-stage pressure & Flow control + Remote




**AXIAL PISTON PUMP****PQ SERIES****DIMENSION****PQ38CR, PQ42CR - 2-stage pressure & Flow control + Low tension unloading****PQ38D, PQ42D - Low tension unloading + Pressure control****PQ38DG, PQ42DG - Low tension unloading + Pressure control + Remote**

# AXIAL PISTON PUMP


## PQ SERIES

### DIMENSION


**PQ38E, PQ42E** - Electric 2-stage pressure control



**PQ38EG, PQ42EG** - Electric 2-stage pressure control + Remote



**PQ38F, PQ42F** - Electric 2-stage pressure control & Flow control




## AXIAL PISTON PUMP


## PQ SERIES

### DIMENSION


**PQ38FG, PQ42FG** - Electric 2-stage pressure control & Flow control + Remote



**PQ38GM, PQ42GM** - Remote pressure compensator with NG6 interface



**PQ38GJ, PQ42GJ** - Remote pressure compensator + Proportional pressure valve




## AXIAL PISTON PUMP


## PQ SERIES

### DIMENSION


**PQ38GR, PQ42GR** - Remote pressure compensator + Electrical unloading



**PQ38GB, PQ42GB** - Remote pressure compensator + 2-stage pressure control



**PQ38GC, PQ42GC** - Remote pressure compensator + Electrical unloading + 2-stage pressure control




## AXIAL PISTON PUMP


### PQ SERIES

#### DIMENSION

**PQ38HQ, PQ42HQ** - Load-sensing compensator + Proportional flow valve + Relief valve




**PQ38HK, PQ42HK** - Load-sensing compensator + Proportional pressure valve + Proportional flow valve



**PQ38, PQ42** - Thru drive (SAE A Ø82.55, code D)  
Thru drive (SAE B Ø101.6, code E)

Type	A	B	C	CG	CR	D	DG	E	EG	F	FG	G	GJ	GM	HL	HK	HQ
○ Thru drive option	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>														




## AXIAL PISTON PUMP


## PQ SERIES

### DIMENSION

**PQ38, PQ42** - Rear port (Please following order code no.6, add "B")




**PQ38, PQ42** - 4 connections for rear port (Please following order code no.6, add "B2")




Type	A	B	C	CG	D	DG	E	EG	F	FG	G	GJ	GM	HL	HK	HQ
○ Axial port option	○	○	○	○					○	○	○	○	○	○		

**PQ38, PQ42** - Splined shaft type



**PQ38, PQ42** - Inlet / Outlet




## AXIAL PISTON PUMP


## PQ SERIES

### DIMENSION


**PQ50A, PQ70A** - Standard pressure control



**PQ50G, PQ70G** - Remote pressure control



**PQ50HL, PQ70HL** - Load-sensing control




## AXIAL PISTON PUMP

## PQ SERIES


### DIMENSION

**PQ50B, PQ70B** - Multi-stage flow & Single-stage pressure control (with cylinder)




**PQ50C, PQ70C** - 2-stage pressure & Flow control

**PQ50CG, PQ70CG** - 2-stage pressure & Flow control + Remote



**PQ50CR, PQ70CR** - 2-stage pressure & Flow control + Low tension unloading




## AXIAL PISTON PUMP

### PQ SERIES

#### DIMENSION


**PQ50D, PQ70D** - Low tension unloading + Pressure control

**PQ50DG, PQ70DG** - Low tension unloading + Pressure control + Remote




**PQ50E, PQ70E** - Electric 2-stage pressure control

**PQ50EG, PQ70EG** - Electric 2-stage pressure control + Remote



**PQ50F, PQ70F** - Electric 2-stage pressure control & Flow control

**PQ50FG, PQ70FG** - Electric 2-stage pressure control & Flow control + Remote




## AXIAL PISTON PUMP


## PQ SERIES

### DIMENSION


**PQ50GM, PQ70GM** - Remote pressure compensator with NG6 interface



**PQ50GJ, PQ70GJ** - Remote pressure compensator + Proportional pressure valve



**PQ50GR, PQ70GR** - Remote pressure compensator + Electrical unloading




## AXIAL PISTON PUMP


### PQ SERIES

#### DIMENSION


**PQ50GB, PQ70GB** - Remote pressure compensator + 2-stage pressure control



**PQ50GC, PQ70GC** - Remote pressure compensator + Electrical unloading + 2-stage pressure control



**PQ50HQ, PQ70HQ** - Load-sensing compensator + Proportional flow valve + Relief valve




# AXIAL PISTON PUMP


## PQ SERIES

### DIMENSION

**PQ50HK, PQ70HK** - Load-sensing compensator + Proportional pressure valve + Proportional flow valve



**PQ50, PQ70** - Thru drive (SAE A  $\phi 82.55$ , SAE B  $\phi 101.6$ , code D or E)




Type	A	B	C	CR	CG	D	DG	E	EG	F	FG	G	GJ	GM	HL	HK	HQ
<input type="radio"/> Thru drive option	<input type="radio"/>					<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>			<input type="radio"/>					

# AXIAL PISTON PUMP

## PQ SERIES

### DIMENSION


**PQ50, PQ70** - Rear port (Please following order code no.6 add "B")



Type	A	B	C	CR	CG	D	DG	E	EG	F	FG	G	GJ	GM	HL	HK	HQ
<input type="radio"/> Thru drive option	<input type="radio"/>																

**PQ50, PQ70** - Splined shaft type


**PQ50, PQ70** - Inlet / outlet



# AXIAL PISTON PUMP


**PQ SERIES**

## PUMP COMBINATION - COUPLING



⑥Coupling	⑦ Snap ring	Depending 2nd pump to use snap ring or not (● : With snap ring)			⑧Screw
		Piston pump: PQ15~18, AR16	Gear pump: HGP- 3A	Vane pump: F30, F40	
COUP - PQ15+15	R13	●	●	●	--
COUP - PQ23-1	R13	●	●		--
COUP - PQ23-3	R20	●			--
COUP - PQ23-5	R20			●	M5 x8
COUP - PQ23-6	--				M5 x8
COUP - PQ38-1	R13	●	●		--
COUP - PQ38-3	R20	●			--
COUP - PQ38-4	--				--
COUP - PQ38-5	R20			●	M5 x8
COUP - PQ38-6	--				M5 x8
COUP - PQ38-7	--				M5 x8
COUP - PQ70-1	R13	●	●		--
COUP - PQ70-3	R20	●			--
COUP - PQ70-4	--				--
COUP - PQ70-5	R20			●	M5 x8
COUP - PQ70-6	--				M5 x8
COUP - PQ70-7	--				M5 x8

③ O-ring	G55
④Pin	ø8x16 x2 nos
⑤Screw	M8x30 x4 nos




## AXIAL PISTON PUMP


**PQ SERIES**

### PUMP COMBINATION - TRU DRIVE DIMENSION

**PQ15, PQ18**



**PQ23~PQ70**



Model	2nd Pump	A	B	C	D	E	F	G
<b>PQ15, PQ18</b>	SAE A	Ø82.55	8.35	--	--	--	106.3	M10xP1.5
	SAE A	Ø82.55	8.35	Ø127	89.8	M10xP1.5	106.3	M10xP1.5
<b>PQ23~ PQ70</b>	SAE A	Ø101.6	10	Ø127	89.8	M10xP1.5	146	M12xP1.75
	Metric	Ø100	10	Ø125	88.39	M10xP1.5	140	M12xP1.75
	Vane Pump	Ø95.02	8.35	--	90	M10xP1.5	--	--

Model	K	H	J	M	L	L2		
<b>PQ15, PQ18</b>	33	13.5	9T 16/32 DP	--	185	--		
<b>PQ23, PQ25</b>	59	13.5	9T 16/32 DP	32	237	205		
<b>PQ38, PQ42</b>	66	20	14T M1.25	32	241	209		
<b>PQ50, PQ70</b>	64.4	22	13T 16/32DP	32	332	300		


# AXIAL PISTON PUMP

**PQ SERIES**

## PUMP COMBINATION - TRU DRIVE DIMENSION


### VIEW A

**PUMP 1 PQ15, PUMP 2 PQ15**



### VIEW B

**PUMP 1 PQ23~PQ70, PUMP 2 PQ15~PQ38**



# AXIAL PISTON PUMP

## PQ SERIES

### PUMP COMBINATION - TRU DRIVE DIMENSION

Pump 1	Pump 2	A	B		C	D	E	F	G	H	I
PQ15, PQ18	PQ15, PQ18	G 3/8" (RC 3/8")	G 3/8" (RC 3/8")		57.45	35.1	35.1	35.1	35.1	M8xP1.25x20	M8xP1.25x20
PQ23, PQ25	PQ15, PQ18	G 3/8" (RC 3/8")	G 3/8" (RC 3/8")		57.45	35.1	35.1	52.4	26.2	M8xP1.25x20	M10xP1.5x16
PQ38, PQ42	PQ23, PQ25	G 3/8" (RC 3/8")	G 3/8" (RC 3/8")		61	52.4	26.2	52.4	26.2	M10xP1.5x16	M10xP1.5x16
PQ38, PQ42	PQ15, PQ18	G 3/8" (RC 3/8")	G 1/2" (RC 1/2")		57.45	35.1	35.1	58.7	30.2	M8xP1.25x20	M10xP1.5x16
PQ38, PQ42	PQ23, PQ25	G 3/8" (RC 3/8")	G 1/2" (RC 1/2")		61	52.4	26.2	58.7	30.2	M10xP1.5x16	M10xP1.5x16
PQ38, PQ42	PQ38, PQ42	G 1/2" (RC 1/2")	G 1/2" (RC 1/2")		73	58.7	30.2	58.7	30.2	M10xP1.5x16	M10xP1.5x16
PQ50, PQ70	PQ15, PQ18	G 3/8" (RC 3/8")	G 3/4" (RC 3/4")		57.45	35.1	35.1	69.9	35.7	M8xP1.25x20	M12xP1.75x25
PQ50, PQ70	PQ23, PQ25	G 3/8" (RC 3/8")	G 3/4" (RC 3/4")		61	52.4	26.2	69.9	35.7	M10xP1.5x16	M12xP1.75x25
PQ50, PQ70	PQ38, PQ42	G 1/2" (RC 1/2")	G 3/4" (RC 3/4")		73	58.7	30.2	69.9	35.7	M10xP1.5x16	M12xP1.75x25

Pump 1	Pump 2	J	K	L	LA	LB	M	N	O	P	Q	R	S	T	U
PQ15, PQ18	PQ15, PQ18	147	147	332	185	—	382	48	48	6	4.76x32	13	Ø19.05	21.15	Ø82.55
PQ23, PQ25	PQ15, PQ18	147	170	384	237	32	411	48	51	9	6.35x40	14	Ø22.22	25.08	Ø101.6
PQ23, PQ25	PQ23, PQ25	170	170	407	237	32	455	51	51	9	6.35x40	14	Ø22.22	25.08	Ø101.6
PQ38, PQ42	PQ15, PQ18	147	179	388	241	32	438	48	51	9	6.35x40	14.5	Ø22.22	25.08	Ø101.6
PQ38, PQ42	PQ23, PQ25	170	179	411	241	32	464	51	51	9	6.35x40	14.5	Ø22.22	25.08	Ø101.6
PQ38, PQ42	PQ38, PQ42	179	179	420	241	32	473	51	51	9	6.35x40	14.5	Ø22.22	25.08	Ø101.6
PQ50, PQ70	PQ15, PQ18	147	256.5	479	332	32	529	48	73	10	7.94x45	24	Ø31.75	35.35	Ø127
PQ50, PQ70	PQ23, PQ25	170	256.5	502	332	32	555	51	73	10	7.94x45	24	Ø31.75	35.35	Ø127
PQ50, PQ70	PQ38, PQ42	179	256.5	511	332	32	564	51	73	10	7.94x45	24	Ø31.75	35.35	Ø127

Pump 1	Pump 2	V	W	X	Y	Z	A1	A2	A3	A4	A5	A6	A7	A8	A9
PQ15, PQ18	PQ15, PQ18	Ø25	Ø25	106	131	165	44	31.2	5	84	11	44.5	160	91.5	60
PQ23, PQ25	PQ15, PQ18	Ø25	Ø25	146	146	182	39	31.2	5	110	13.5	58.5	193	93	68
PQ23, PQ25	PQ23, PQ25	Ø25	Ø25	146	146	182	39	31.2	5	110	13.5	58.5	193	93	68
PQ38, PQ42	PQ15, PQ18	Ø31	Ø31	146	160	198.6	39	31.2	5	121	13.5	58.5	210	113.5	72
PQ38, PQ42	PQ23, PQ25	Ø31	Ø31	146	160	198.6	39	31.2	5	121	13.5	58.5	210	113.5	72
PQ38, PQ42	PQ38, PQ42	Ø31	Ø31	146	160	198.6	39	31.2	5	121	13.5	58.5	210	113.5	72
PQ50, PQ70	PQ15, PQ18	Ø38	Ø38	181	208	261.5	74	40	8	119	18	57	233.5	133.5	100
PQ50, PQ70	PQ23, PQ25	Ø38	Ø38	181	208	261.5	74	40	8	119	18	57	233.5	133.5	100
PQ50, PQ70	PQ38, PQ42	Ø38	Ø38	181	208	261.5	74	40	8	119	18	57	233.5	133.5	100

## NOTES

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

## RANGE OF PRODUCTS



**SINGLE • DOUBLE • THRU-DRIVE VANE PUMPS**



**VARIABLE DISPLACEMENT PUMP HSP-10V**



**DIRECTIONAL CONTROL VALVE**

hydraut

[hydraut.com](http://hydraut.com)